



Technical Data Sheet for Europe, Middle East and Africa

PRIMAL™ AC-339 Acrylic Emulsion Polymer

Product Description

PRIMAL™ AC-339 Acrylic Emulsion Polymer is a very hydrophobic APEO-free* acrylic emulsion polymer. Its versatility makes it suitable for a wide variety of applications, like primers, sealer and coatings for cementitious substrates and highly wear resistant marble stone finishes.

*APEO is not intentionally added and is not knowingly introduced from another raw material.

Application

Due to its hydrophobic character PRIMAL™ AC-339 Acrylic Emulsion Polymer provides remarkable resistance to water whitening and water pick-up. It shows excellent resistance to efflorescence from fresh cement substrate and high resistance to hydrophilic stains.

PRIMAL AC-339 Acrylic Emulsion Polymer is resistant against alkali and gives good adhering films on chalk and cementitious substrates. Coatings and primers/sealers based on PRIMAL AC-339 Acrylic Emulsion Polymer requires moderate amount of coalescent and has a high early block resistance. A blend of Butyl Glycol and DOWANOL™ DPnB product (8:2) at 10% on polymer solids is suggested.

Typical Properties¹⁾

Appearance	Milky white liquid
MFFT	28 °C
Solids content	47.5 ... 48.5 %
pH	7.7 ... 8.7
Density	1.06 g/cm ³
Viscosity (Brookfield LV, spindle 2 @ 30 rpm, 25°C)	max. 800 mPa·s

¹⁾ Please note that the values shown are typical values for your guidance. They are not to be taken as specifications and are subject to certain variability. Please consult the sales specifications for details.

Health and Safety Considerations

Safety Data Sheets (SDS) are available from The Dow Chemical Company. SDS are provided to help customers satisfy their own handling, safety and disposal needs and those that may be required by locally applicable health and safety regulations. SDS are updated regularly, therefore, please request and review the most current SDS before handling or using any product. For further questions consult your Dow contact person.

Storage and Handling

PRIMAL™ AC-339 Acrylic Emulsion Polymer should be stored at temperatures between 5°C and 40°C in tightly sealed containers. Avoid freezing of the material! Local legislation on storage must be followed.

PRIMAL™ AC-339 Acrylic Emulsion Polymer is protected against microbial attack during transportation and storage in not opened original packaging. To avoid problems with microbial attack during processing and in opened packaging attention should be paid on hygiene. In some cases it could make sense to add biocides to avoid problems with microorganisms.

We recommend using the product under safety precautions as described in the SDS. Avoid contact with eyes and skin. Large quantities should be handled in a correctly ventilated area. Material can create slippery conditions.

As the product contains water corrosion-resistance equipment should be used for processing. Low shear pumps like diaphragm pumps should be used.

Product Stewardship

Dow has a fundamental concern for all who make, distribute and use its products, and for the environment in which we live. This concern is the basis for our Product Stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our Product Stewardship program rests with each and every individual involved with Dow products — from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.

Customer Notice

Dow strongly encourages its customers to review both their manufacturing processes and their applications of Dow products from the standpoint of human health and environmental quality to ensure that Dow products are not used in ways for which they are not intended or tested. Dow personnel are available to answer your questions and to provide reasonable technical support. Dow product literature, including safety data sheets, should be consulted prior to use of Dow products. Current safety data sheets are available from Dow.

Additional Information	<p>For more information you may call the following numbers:</p> <table> <tr> <td>Europe*)</td> <td>+800-3-694-6367 (toll free)</td> </tr> <tr> <td>Italy</td> <td>800-783-825 (toll free, national)</td> </tr> <tr> <td>Europe, Middle East, Africa</td> <td>+31-11567-2626 (toll call)</td> </tr> <tr> <td>South Africa</td> <td>+800-99-5078 (toll free, national)</td> </tr> </table> <p>*) International toll free from Austria, Belgium, Denmark, Finland (prefix 990), France, Germany, Hungary, Ireland, The Netherlands, Norway, Portugal, Spain, Sweden, Switzerland, and the United Kingdom.</p>	Europe*)	+800-3-694-6367 (toll free)	Italy	800-783-825 (toll free, national)	Europe, Middle East, Africa	+31-11567-2626 (toll call)	South Africa	+800-99-5078 (toll free, national)
Europe*)	+800-3-694-6367 (toll free)								
Italy	800-783-825 (toll free, national)								
Europe, Middle East, Africa	+31-11567-2626 (toll call)								
South Africa	+800-99-5078 (toll free, national)								

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

